

Sealed bids, clearly marked Town of Outlook – Mahindra Tractor will be received at the Town of Outlook Municipal Office, 400 Saskatchewan Avenue West or mailed to PO Box 518, Outlook, Saskatchewan, S0L 2N0 prior to 4:00pm, September 14th, 2023. Bids will be opened and read at the Town of Outlook Municipal Office on September 20th, 2023 at 4:00 pm.

The equipment up for tender includes:

2014 Mahindra Tractor Compact
60" mower
60" tiller
Farm King Y604BS Box Scraper
1410.4 Hours
Last serviced at 1410.4 hours

Facility Supervisor, Owen Redlick will be the main contact for questions or viewing. Please email recfacilities.outlook@sasktel.net or call the Recreation Department at 306-867-9555.

Interested bidders may attend the site to inspect the equipment on September 7th, 2023 between 5:00pm-6:00pm at the Jim Kook RecPlex. For an alternative date and time please contact Owen Redlick at the above contact information.

As part of this tender process the Town of Outlook, and its representatives, makes no obligations in any way to:

- (i) Pay any vendor for any Invitation to Tender response; or
- (ii) Award the sale to the highest or any bidder; or
- (iii) Accept any Invitation to Tender information received from buyers; or
- (iv) Include buyers responding to the Invitation to Tender, in any future invitation; or
- (v) Any other commitment to buyers whatsoever

Bid Summary



Spec document attached

Total Bid \$ _____

This bid is executed under seal at _____ this _____ day of _____, 2023.

Name of firm or individual

Address

Signature

Phone:

Email address

Contact Person

Highest or any tender not necessarily accepted.



Engine

- Achieve rated HP at lower RPM than competition
- Less wear; Less maintenance
- Longer engine life

TRACTOR MODEL	MAHINDRA MAX 28XL HST	KUBOTA L3200	JOHN DEERE 3032E	NEW HOLLAND BOOMER 30
Cylinders	3	3	3	4
Engine HP (kW) @ RPM	28 (20.8) @ 2600	31.9 (23.5) @ 2600	31.4 (23.1) @ 2600	28 (21) @ 2600
Displacement in ³ (cc)	80.4 (1318)	91.5 (1480)	87.8 (1300)	82 (1500)
PTO RPM	540 @ 2275	540 @ 2430	540 @ N/A	540 @ N/A
Mid PTO RPM	2000 @ 2525 (Optional)	N/A	N/A	2000 @ N/A

Transmission

- Smooth operation controls
- Quiet operation
- 10 mph top speed

TRACTOR MODEL	MAHINDRA MAX 28XL HST	KUBOTA L3200	JOHN DEERE 3032E	NEW HOLLAND BOOMER 30
Type	HST – 2 range	HST – 3 range	HST – 2 range	HST – 3 range
Number of Speeds	Infinite	Infinite	Infinite	Infinite

Hydraulics

- Best-in-Class lift capacity
- Higher pump output
- Responsive hydraulic controls
- Optional rear remote

TRACTOR MODEL	MAHINDRA MAX 28XL HST	KUBOTA L3200	JOHN DEERE 3032E	NEW HOLLAND BOOMER 30
Type	Open center, full flow hydraulic with position control	Open center, full flow hydraulic with position control	Open center, full flow hydraulic with position control	Open center, full flow hydraulic with position control
Total Pump Output, Main (gallons per minute)	4.8	6.5	5.3	6.2
Total Pump Output, Steering (gallons per minute)	2.7	4	4	4.1
Lift Capacity (lbs)	2205	1988	1350 @ 24" behind pins	1807

Specifications accurate at time of printing. Subject to change without notice.

Operating Weight

- Best-in-Class operating weight
- Heavy-duty chassis; Great traction & stability
- Large stance gives added assurance while transferring power to the ground

TRACTOR MODEL	MAHINDRA MAX 28XL HST	KUBOTA L3200	JOHN DEERE 3032E	NEW HOLLAND BOOMER 30
Total (lbs)	1863	2623	2067	2913
DIMENSIONS:				
Overall Length inches (mm)	109.3 (2775)	106.5 (2705) w/o Spt. linkage	111 (2820)	91 (2291)
Overall Width inches (mm)	54.3 (1380)	55.1 (1400)	56.5 (1434)	64 (1618)

Tires

- Available in Ag, Industrial or Turf

TRACTOR MODEL	MAHINDRA MAX 28XL HST	KUBOTA L3200	JOHN DEERE 3032E	NEW HOLLAND BOOMER 30
Ag (Front / Rear)	7x12 / 9.5x16	7-16 / 11.2-24	7-14 / 11.2-24	7x14 / 11.2x24
Industrial (Front / Rear)	23x8.5-12 / 12x16.5	27x8.5-15 / 15-18.5	25x8.5-14 / 15-18.5	25x8.5-14 / 43x18-20
Turf (Front / Rear)	23x8.50-12 / 33x12.5x16.5	25x8.5-14 / 13.8-16	27x8.5-15 / 41x14-20	25x8.5-14 / 41x14-20

Loader

- One of the best-in-class lift capacity
- Superior Performance; Rugged design

TRACTOR MODEL	MAHINDRA MAX 28XL HST	KUBOTA L3200	JOHN DEERE 3032E	NEW HOLLAND BOOMER 30
Model No.	ML205	LAS4	305	240TL
Maximum Lift Height (in)	82.7	94.3	84	97.8
Digging Depth (in)	2.8	6.9	N/A	8.5
Lift Capacity to Full Height @ Pivot Pin (lbs)	1402	1131	1168	1370
Breakout Force @ Pivot Pin (lbs)	2690	2462	1704	2526

Notes

TRACTOR MAX 28XL HST

ENGINE	
Type	Four stroke, indirect injection water-cooled, diesel
Cylinders	3
Engine HP (kW) @ rpm	28 (20.8) @ 2600
Compression Ratio	22:1
Displacement cubic inch (cc)	80.4 (1318)
Fuel Tank Capacity	6.1 gallons
ELECTRICAL	
Battery Capacity	12 volt, 35 amp hours
Alternator	12 volt, 50 amps
CLUTCH	
Type	Single plate, dry
TRANSMISSION	
Type	HST - 2 ranges
Number of Gears / Speeds	Infinite
STEERING	
Type	Hydrostatic Power
Pump Output (gallons per minute)	2.7
BRAKES	
Type	Wet disc
HYDRAULIC SYSTEM	
Type	Open center, full live hydraulic with position control
Pump Output (gallons per minute)	4.6
3-Point Linkage	Category 1, with check chains
Lift Capacity (lbs.)	2205
Rear Auxiliary Remote Valves	1 spool optional
PTO	
Type	Trans
PTO RPM (engine rpm)	540 @ 2376
Mid PTO RPM (engine rpm)	2000 @ 2526
PTO HP (kW)	22 (16.4)
OPERATING WEIGHT	
Total (lbs.)	1863
DIMENSIONS With Ag Tires	
Overall Length inches (mm)	109.3 (2775)
Overall Width inches (mm)	54.3 (1380)
Turning Radius Minimum feet (meters)	6.6 (2.0)
TIRES Sizes & Options	
Ag (Front / Rear)	7x12 / 9.5x16
Industrial (Front / Rear)	23x8.5-12 / 12x16.5
Turf (Front / Rear)	23x8.5-12 / 33x12.5-16.5

LOADER ML205

WITH TRACTOR MODEL MAX 28XL HST	
Maximum Lift Height	82.7"
Clearance with Attachment Dumped	67.3"
Reach at Maximum Height	29"
Maximum Dump Angle	32°
Attachment Rollback Angle	24°
Digging Depth Below Grade	2.6"
Lift Capacity to Full Height @ Pivot Pins (lbs.)	1402
Breakout Force @ Pivot Pins (lbs.)	2690
Rated Flow (Tractor System)	4.6 gpm
Attachment Width used for specification	48"
Attachment Rated Capacity used for specification	7 cu. ft.
Cycle Times @ rpm	2600
Raise Boom (seconds)	3.3
Lower Boom (seconds)	2.4
Dump Attachment (seconds)	2.2
Retract Attachment (seconds)	2.6
Loader Shipping Weight (lbs.)	627.2

BACKHOE

WITH TRACTOR MODEL MAX 28XL HST	
Backhoe Model	MB63A
TRANSPORT	
Stabilizer Spread, up position	58"
Transport Height (maximum)	70"
Transport Overhang	37"
OPERATIONAL	
Maximum Digging Depth	76.3"
Digging Depth (2 Ft.) Flat Bottom	74.9"
Loading Height (bucket at 60°)	62"
Loading Reach (bucket at 60°)	36"
Reach from Center Line of Swing Pivot	102"
Bucket Rotation	180°
Swing Arc	150°
Stabilizer Spread, fully extended	74"
Digging Force - Bucket (lbs.)	2145
Digging Force - Dipper (lbs.)	903
Hydraulic Pressure Requirements (psi)	2000
Hydraulic Volume Requirements	2-4 gpm
Undercut	16"